

Ceiling White Paint - Technical Data Sheet

Product Description

Supercoat™ Ceiling White is an acrylic coating for use on internal ceilings. Supercoat™ Ceiling White is a highly durable premium Ceiling White using long life coating technologies. It provides excellent coverage, is easy to apply and flows on with a brush or roller. This product can also be spray applied. For use on primed fibre and particle boards, Styrofoam panels, wallpaper, timber and modified plaster.

Specifications

MSDS	009 - Version 1.0
Appearance	White
Vehicle Type	Styrene Acrylic
Pigmentation	Titanium Dioxide
Solvent	Water
Finish	Flat
Touch dry time	25 minutes at 20°C
Time to 2nd coat	2 hours at 20°C
Wet film thickness	50 microns
Solids Content	40.6 - 47.6%
Viscosity	95 - 105 KU
Specific Gravity	1.03 - 1.4
Usual number of coats	2 - 3 (depending on substrate and colour density)
Toxicity	No added Chromites or Lead
Thinning & cleaning	Water
Coverage	8 - 12m ² /L depending on substrate profile and applicator
Pail type & size	Plastic 4L, 8L & 20L

Please Note

Do not apply at temperatures below 10°C or if it is likely to drop below 10°C during drying/curing time. Do not apply at temperatures over 30°C or if it is likely to go over 30°C during drying/curing time. Softens at temperatures over 70°C.

Manufacturer

Ironbark Technology Ltd
PO Box 2398, Dunedin, New Zealand.
Phone (03) 456 4222
info@ironbark.technology

The information contained herein is correct to the best of our knowledge. Due to product improvement and supply, these specifications may be subject to minor changes.