

## Galvcoat Primer - Technical Data Sheet

### Product Description

Supercoat™ Galvcoat Primer is a highly durable Styrene Acrylic using long life protective coating technologies. Galvcoat Primer provides excellent coverage, is easy to apply and flows on with a brush or roller. This product can also be applied by airless spray. For use on Galvanised steel and other suitable substrates.

### Specifications

<b>MSDS</b>	<b>011 - Version 1.0</b>
<b>Appearance</b>	Grey
<b>Vehicle Type</b>	Styrene Acrylic
<b>Solvent</b>	Water
<b>Touch dry time</b>	25 minutes at 20°C
<b>Time to 2<sup>nd</sup> coat</b>	2 hours at 20°C
<b>Wet film thickness</b>	200 microns (airless spray)
<b>Solids Content</b>	40.6 - 47.6%
<b>Viscosity</b>	75 - 90KU
<b>Specific Gravity</b>	1.18 - 1.3
<b>Usual number of coats</b>	1 (depending on substrate and colour density)
<b>Toxicity</b>	No added Chromites or Lead
<b>Thinning &amp; cleaning</b>	Water
<b>Coverage</b>	12 - 15m <sup>2</sup> /L via brush or roller, 5m <sup>2</sup> /L via airless spray (depending on substrate profile and applicator)
<b>Pail type &amp; size</b>	Plastic 4, 8 & 20L

### Please Note

Do not apply at temperatures below 10°C or if it is likely to drop below 10°C during drying/curing time. Do not apply at temperatures over 30°C or if it is likely to go over 30°C during drying/curing time. Softens at temperatures over 70°C. Safe to use on surfaces that collect drinking water.

### Manufacturer

**Ironbark Technology Ltd**  
PO Box 2398, Dunedin, New Zealand.  
Phone (03) 456 4222  
info@ironbark.technology