

Galvcoat Topcoat - Technical Data Sheet

Product Description

Supercoat™ Galvcoat Topcoat is a highly durable Acrylic using long life protective coating technologies. Galvcoat Topcoat provides excellent coverage, is easy to apply and flows on with a brush or roller. This product can also be applied by airless spray. For use on Galvanised steel over Supercoat™ Galvcoat Primer or stable previously coated substrates.

Specifications

MSDS	012 - Version 1.0
Appearance	16 standard colours
Vehicle Type	Acrylic
Colour	16 standard colours
Primer	Galvcoat Primer (not required over <u>stable</u> previously coated substrates)
Solvent	Water
Touch dry time	30 minutes at 20°C
Time to 2nd coat	2 hours at 20°C
Wet film thickness	250 microns (airless spray)
Solids Content	40.6 - 47.6%
Viscosity	85 - 100KU
Specific Gravity	1.18 - 1.3
Usual number of coats	2 via brush, 1 via airless spray (depending on substrate and colour density)
Toxicity	No added Chromites or Lead
Thinning & cleaning	Water
Coverage	12 - 15m ² /L via brush, 5m ² /L via airless spray (dependant on substrate profile and applicator)
Pail type & size	Plastic 4L, 8L & 20L

Please Note

Do not apply at temperatures below 10°C or if it is likely to drop below 10°C during drying/curing time. Do not apply at temperatures over 30°C or if it is likely to go over 30°C during drying/curing time. Softens at temperatures over 70°C. Safe to use on surfaces that collect drinking water.

Manufacturer

Ironbark Technology Ltd
PO Box 2398, Dunedin, New Zealand.
Phone (03) 456 4222
info@ironbark.technology