

Platinum Series Paint - Technical Data Sheet

Product Description

Supercoat™ Platinum Series is a multipurpose pure acrylic interior/exterior Paint for use on AAC, wallboards, fibre & particle boards, timber, wallpaper, weatherboards, block work, stucco roughcast plaster, concrete, EPS and modified plasters.

Specifications

MSDS	001 - Version 1.0
Appearance	White to Mid Cream
Vehicle Type	Acrylic
Pigmentation	Titanium Dioxide
Solvent	Water
Finish	Gloss, Semi Gloss, Low Sheen, Flat
Colour	Fully tintable
Touch dry time	25 minutes at 20°C
Time to 2nd coat	24 hours at 20°C
Wet film thickness	50 microns
Solids Content	40.6 - 47.6%
Viscosity	95 - 105 KU
Specific Gravity	1.03 - 1.4
Usual number of coats	2 - 3 (depending on base, substrate and colour density)
Toxicity	No added Chromites or Lead
Thinning & cleaning	Water
Coverage	6 - 12m ² /L (depending on substrate profile and applicator)
Pail type & size	Plastic 4L, 8L & 20L

Please Note

Do not apply at temperatures below 10°C or if it is likely to drop below 10°C during drying/curing time. Do not apply at temperatures over 30°C or if it is likely to go over 30°C during drying/curing time. Softens at temperatures over 70°C.

Manufacturer

Ironbark Technology Ltd
PO Box 2398, Dunedin, New Zealand.
Phone (03) 456 4222
info@ironbark.technology