

Primer Sealer Undercoat - Technical Data Sheet

Product Description

Supercoat™ Primer Sealer Undercoat is a highly durable Styrene Acrylic. Primer Sealer Undercoat provides excellent coverage, is easy to apply and flows on with a brush, roller or via airless spray. This product can be sanded for the perfect finish. For use on wallboards, fibre and particle boards, wallpaper, timber and weatherboards.

Specifications

MSDS	013 - Version 1.0
Appearance	White
Vehicle Type	Styrene Acrylic
Pigmentation	Titanium Dioxide
Solvent	Water
Touch dry time	30 minutes at 20°C
Time to 2nd coat	2 hours at 20°C
Dry film thickness	25 microns
Solids Content	40.6 - 47.6%
Viscosity	95 - 105 KU
Specific Gravity	1.03 - 1.4
Usual number of coats	1 (depending on substrate and colour density)
Toxicity	No added Chromites or Lead
Thinning & cleaning	Water
Coverage	6-12m ² /L (depending on substrate profile and applicator)
Pail type & size	Plastic 4L, 8L & 20L

Please Note

Do not apply at temperatures below 10°C or if it is likely to drop below 10°C during drying/curing time. Do not apply at temperatures over 30°C or if it is likely to go over 30°C during drying/curing time. Softens at temperatures over 70°C.

Manufacturer

Ironbark Technology Ltd
PO Box 2398, Dunedin, New Zealand.
Phone (03) 456 4222
info@ironbark.technology